

Space Station / Shuttle / Mars Electronics Space Weather Forecast Requirements

EA44/Pat O'Neill Johnson Space Center (281) 483-5180 poneill@ems.jsc.nasa.gov February 9, 2000



JSC Missions

EA44/Station Engineering Office	
Pat O'Neill	02/09/00

- Space Shuttle (150 350 nmi, to 57 deg)
 - Avionics Upgrades (flight computers, displays, mass storage, etc.)
- International Space Station (Low Earth Orbit 51.6 deg)
 - US, Canadian, Russian, Europeans, Japanese
- Mars /01, /03
 - Mars In-Situ Propellant Production (MIPS)
 - Mars Radiation Environment Experiment (MARIE)
- Government Furnished Equipment (GFE)
 - avionics common to Space Station & Shuttle
 - GPS Navigation, laptops, EVA, communications with ISS



Space Shuttle Electronics - Our Space Weather Program

EA44/Station Engineering Office		
Pat O'Neill	02/09/00	

- New General Purpose Flight Computers installed on STS-37 (April 1991)
 - SRAM memory susceptible to soft errors, EDAC corrects and time tags
 - Since STS-37: 56 STS missions, 570 days on-orbit, 7000 single event upsets
 - SEU's correlate with geomagnetic cutoff and South Atlantic Anomaly
 - No major solar flares, no direct correlation with space weather
 A major solar flare could cause excessive SEU's



Space Shuttle Electronics - Our Space Weather Program

EA44/Station Engineering Office

Pat O'Neill

02/09/00

ACTUAL SEU'S - QUIET SUN & GEOMAGNETIC FIELD

SIMULATED - MAJOR SOLAR FLARE, NO GEOMAGNETIC FIELD



ISS Electronics - Our Space Weather Program

EA44/Station E	ngineering Office
Pat O'Neill	02/09/00

- ISS Avionics: Command & Data Handling, Comm & Track, Environment & Life Support, Power, Robotics, Thermal Control
 - Safety-Critical hardware that must remain powered and operational - low Single Event Latch-up (SEL) susceptibility
 - > 400 equipment items susceptible to SEL that can (& should be) powered down in the event of a large solar flare
- Russian, European, Japanese no data available!



Mars /01 /03 Electronics - Our Space Weather Program

EA44/Station Engineering Office	
Pat O'Neill	02/09/00

- Mars In-Situ Propellant Production (MIPS)
 - powered off during transit to Mars
 - powered up after landing on Mars surface
 - 16 g /cm**2 of atmosphere
- Mars Radiation Environment Experiment (MARIE)
 - must operate in orbit and on surface
 - highly exposed to solar flare particles
- components certified by proton testing and flight experience



GFE Electronics - Our Space Weather Program

EA44/Station Engineering Office		
Pat O'Neill	02/09/00	

- GFE Avionics for Shuttle and Space Station:
 Data Processing, Comm & Track, Video systems, ...
 - mostly qualified for space flight by testing with 200 MeV protons
 - 10 yr lifetime reasonably assured for nominal space weather
 - large solar flare with a hard heavy ion spectrum could induce failures not observed in tests



Space Weather measurement products & requirements

EA44/Station Engineering Office

Pat O'Neill

02/09/00

- Highest priority:
 differential energy particle
 spectra as a function of time
 <u>inside / outside</u>
 magnetosphere
- ion species (z=1 to 28)
 (spectra for selected elements would be acceptable helium, protons, oxygen , iron)
- energy (10 to 2000 MeV/n)



Space Weather measurement products & requirements

EA44/Station	Engineering	Office

Pat O'Neill

02/09/00

- Priority 2:
- Geomagnetic weather index (Kp)
- function of time
- Priority 3:
- Early Warning
- Space Station needs time to prepare shut down equipment